

TECHNICAL DATA SHEET

Part No. 170-03140
Article No. 170-03140
Type BSSWFR180B



Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

Material	Polyester (PET)
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Melting Point	+446 °F (+230 °C)
Abrasion Resistance	High
Flammability	UL 224 VW-1, FAR 25
Halogen Free	Yes
UV Resistant	No
Use Conditions	For Indoor and Outdoor Use
Color	Black (BK)
Pkg. Qty.	400 ft
Carton Qty.	4
Customs Number	5808100000

Max. Bundle Diameter (imperial)	0.13 "
Max. Bundle Diameter (metric)	3.2 mm
Min. Bundle Diameter (imperial)	0.1 "
Min. Bundle Diameter (metric)	2.54 mm
Nominal Diameter (imperial)	0.125 "
Nominal Diameter (metric)	3.18 mm
Reel Length (imperial)	400.0 ft
Reel Length (metric)	121.9 m
Wall Thickness (imperial)	0.024 "
Wall Thickness (metric)	0.61 mm

HF ✓

LFH ✓

RoHS ✓

ASTM 